

IQ8TAL with isolator, 1 contact IN/1 OUT



Part-No. 804868

Approval: VdS

The technical alarm device IQ8TAL is a fully-fledged loop device of the IQ8Control fire detection system and facilitates the detection and forwarding of technical alarms.

The IQ8TAL is equipped with an integrated loop isolator, a contact input and a relay output. The integrated relay can be optionally configured as a normally-closed contact or as a normally-open contact. An external NO or NC may be connected to a single IQ8TAL. When an alarm is triggered the address and the programmed additional text of the IQ8TAL to which the contact is connected are displayed automatically. The IQ8TAL does not need a separate voltage supply.

Features:

- One contact input and one floating relay output
- Voltage supply via the field bus
- Test and reset function
- Higher IP55 protection with Part No. 704965
- Programmable inverse monitoring functionality of the contact input (1k resistance latent/10k resistance fire)
- Powered by the FACP
- Total cable length of the external contact up to 500 m
- Integrated loop isolator
- Max. 127 transponder TAL electronic modules per analog loop

In order to increase the IP protection class, the optional IP 55 protection kit (Part No. 704965) can be used.

The functionality of the IQ8TAL can be tested with the included key and the alarm status can be reset directly at the device.

Quiescent current @ 19 V DC	45 µA
Contact load relay	30 V DC/AC/1 A
Alarm display	red LED
Operation indicator	green LED
Application temperature	-20 °C ... 70 °C
Storage temperature	-30 °C ... 75 °C
Connection terminal	max. 2.5 mm ² (AWG 26-14)
Type of protection	IP 43, IP 55 with cover 704965
Housing	PC/ASA plastic
Air humidity	< 95 % (non condensing)
Color	blue, similar to RAL 5015
Weight	approx. 110 g
Specification	EN 54-18 / -17/-13
Dimensions	W: 88 mm H: 88 mm D: 21 mm W: 88 mm H: 88 mm D: 57 mm (with surface-mounted housing)



Please note that for surface mounting, the mount housing (Part No. 704981) must be ordered separately. Compatible with all IQ8Control systems with firmware V3.08 and tools 8000 V1.14 or superior.



2 x 10 k (terminating), 1 x 1 k (alarm), 1 x 6.8 k (inverse operation)

Accessories:

704965 Protective kit for MCP and TAL, transparent

704981 Surface mount housing for small MCP, blue